

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:

Southern Aerosols Inc.
325 Clearview Rd.
PO Box 67
Cleveland, NC 27013

EMERGENCY TELEPHONE NO.

800-535-5053
INFOTRAC

DATE OF PREPARATION:

March 10, 2009

INFORMATION TELEPHONE NO.:

704-278-9800

Section I PRODUCT IDENTIFICATION

PRODUCT BASE NUMBER: (DV-16) 7505

HMIS CODES

Health 2
Flammability 4
Reactivity 0
NFPA Code 30B
Level 3

PACKAGED FOR NAME (S): Michael Weinig

PRODUCT NAME(S): Green Ral 6011

PART NUMBER: 00331607

PRODUCT CLASS: Aerosol Coating (s)

Section II HAZARDOUS INGREDIENTS

INGREDIENT	ACGIH	OSHA	UNITS
Cas No.	TLV	PEL	
Propane	N/E	1000	PPM
74-98-6			
Acetone	750	750	PPM
67-64-1	1000	1000	PPM
STEL			
Methyl Ethyl Ketone	200	200	PPM
78-93-3			
Ethyl 3 Ethoxypropionate	N/E	N/E	PPM
763-69-9			
Xylene	100	100	PPM
1330-20-7			
Ethyl Benzene	100	100	PPM
100-41-4			
Aromatic 100	N/E	100	PPM
64742-95-6			

Section III PHYSICAL DATA

PRODUCT WEIGHT	7.55 lb/gal.	EVAPORATION RATE:	Faster than Ether
SPECIFIC GRAVITY	0.91	VAPOR DENSITY	Heavier than Air
BOILING POINT	0 - 342 °F	HMIS	240
VOLATILE WT.	83.4 % less federally exempt solvents		
VOLATILE VOLUME:	88.0 %		
VOC	2.85 LB/. Gal.	WITHOUT ACETONE	37.8 %

Section IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	LEL	UEL
Propellant <0F	1.0	12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed container may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions over exposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

Section V HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before reuse.

If in EYES Flush eyes with large amount of water for 15 minutes. Get medical attention.

If SWALLOWED Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Seek medical attention.

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI REACTIVITY DATA

STABILITY:

Stable

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY

None Known

HAZARDOUS DECOMPOSITION PRODUCTS:

By fire: Carbon Monoxide, Carbon Dioxide

HAZARDOUS POLYMERIZATION

Will not occur.

Section VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Waste from this product may be hazardous as defined under the Resource Conservation and Recover Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State and Local regulations regarding pollution.

Section VIII PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE:

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain material classified as nuisance particulates (listed "As Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, The applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), OSHA PEL 15 mg/m³ (total dust), 5mg/m³ (respirable fraction).

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure can not be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust, which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated side shields.

Section IX PRECAUTIONS

DOL STORAGE CATEGORY: 1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.
During use and until all vapors are gone: Keep area ventilated, do not smoke, and extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and any other source of ignition.
Consult NFPA code. Use approved Bonding and Grounding procedures.
Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F.
Heat from sunlight, radiators, stoves, hot water and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS:

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X OTHER REGULATORY INFORMATION

SARA 313 (40CFR 372.65C) SUPPLIER NOTIFICATION

Cas. No.	Chemical/Compound	% By Wt.
1330-20-7	Xylene	7.1 %
100-41-4	Ethyl Benzene	1.5 %
78-93-3	Methyl Ethyl Ketone	6.3 %

CALIFORNIA PROPOSITION 65

This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

All components of this product are listed or are exempt from listing on the TSCA Chemical Substance Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to the product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.